

## Vertical Pressure Steam Sterilizer

### Characteristics:

- 1. Fully stainless steel structure.
- 2. Hand wheel type of quick-open door structure.
- 3. Door safety lock system.
- 4. Digital display of working status, touch of key.
- 5. Self-inflating type seal.
- 6. Over temperature & over pressure auto-protection.
- 7. Safe protection of water lacking.
- 8. Automatically shut off with beep reminding after sterilization.
- 9. Auto discharge the cool air, and steam discharging automatically after sterilization.
- 10. Used for sterilization of medical instruments, medical cotton products.
- 11. Fully stainless steel SUS304/AISI 304 -3mm.
- 12. 24 months warranty.
- 13. Possible to install drying system according request.



FSF-28HD



FSF-35HD/50HD/75HD/100HD

### Main Technical Parameters:

Model	FSF-28HD	FSF-35HD	FSF-50HD	FSF-75HD	FSF-100HD
Capacity	28L (Φ270*500)mm	35L (Φ318*450)mm	50L (Φ340*550)mm	75L (Φ400*600)mm	100L (Φ440*650)mm
Working pressure	0.22Mpa				
Working temperature	134℃				
Max. working pressure	0.23Mpa				
Heat average	≤ ± 1℃				
Timer	0~99min or 0~99hour59 min				
Temp. range	105℃~134℃				
Power	2KW/ AC220V.50Hz	2.5KW/ AC:220V.50Hz	3KW/ AC220V.50Hz	4.5KW/AC220V.50Hz	
Exterior size	400*370*700mm	450*450*1010mm	510*470*1130mm	560*560*1120mm	540*560*1250mm
Packing size	440*320*750mm	570*550*1150mm	590*590*1280mm	650*630*1280mm	680*630*1370mm
G.W/N.W	26/23kg	72kg/56kg	88kg/68kg	100kg/80kg	110kg/85kg